

Product datasheet HALOSTAR STARLITE 10 W 6 V G4

HALOSTAR STARLITE | Low-voltage halogen lamps with pin base





Product datasheet

Technical data

Electrical data

| Nominal wattage | 10.00 W |
|--|---------|
| Nominal voltage | 6 V |
| Rated wattage | 10.00 W |
| Claimed equiv. conventional lamp power | 10 W |


Photometrical data

| Nominal luminous flux | 145 lm |
|---------------------------|------------|
| Light color (designation) | Warm White |
| Rated luminous flux | 145 lm |
| Rated color temperature | 2700 К |
| Color rendering index Ra | 100 |
| Color temperature | 2700 К |
| Luminous flux | 145 lm |

Light technical data

| Starting time | 0.0 s |
|---------------|-------|
| building time | 0.0 5 |

Dimensions & weight



| Diameter | 10.0 mm | |
|---------------------------|---------|--|
| Overall length | 33.0 mm | |
| Light center length (LCL) | 22.0 mm | |
| Length | 33.0 mm | |
| Outer bulb | T10 | |
| Product weight | 1.10 g | |

Lifespan

Product datasheet

| Rated lamp life time | 4000 h |
|----------------------------|--------|
| Number of switching cycles | 50000 |

Additional product data

| Base (standard designation) | G4 | |
|-----------------------------|---------------|--|
| Mercury content | 0.0 mg | |
| Mercury-free | Yes | |
| Predecessor EAN | 4050300335131 | |

Capabilities

| Burning position | Any |
|------------------|-----|
| Dimmable | Yes |

Certificates & standards

| Energy efficiency class | G | |
|-------------------------|--------------|--|
| Energy consumption | 11 kWh/1000h | |

Country specific categorizations

| ILCOS | HSGS/C/AXUB-10-6-G4-10/22 | |
|-----------------|---------------------------|--|
| Order reference | 64410 S AX 10W | |

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|-------------------------------------|--|---|----------|--------------|
| 4058075094192 | HALOSTAR STARLITE 10 W 6 V G4 | Shipping carton box 40 Pieces Folding carton box | 144 mm x 107 mm x 121 mm | 1.86 dm³ | 165.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

Product datasheet

OSRAM is distribution partner of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH Marcel-Breuer-Strasse 6 80807 Munich, Germany