
Product datasheet

HALOSTAR STARLITE 20 W 12.0 V G4

HALOSTAR STARLITE | Low-voltage halogen lamps with pin base



Product datasheet

Technical data

Electrical data

Nominal wattage	20.00 W
Nominal voltage	12 V
Rated wattage	20.00 W
Claimed equiv. conventional lamp power	20 W


Photometrical data

Nominal luminous flux	375 lm
Light color (designation)	Warm White
Rated luminous flux	375 lm
Rated color temperature	2800 K
Color rendering index Ra	100
Color temperature	2800 K
Luminous flux	375 lm

Light technical data

Starting time	0.0 s
---------------	-------

Dimensions & weight



Diameter	10.0 mm
Overall length	33.0 mm
Light center length (LCL)	22.0 mm
Length	33.0 mm
Outer bulb	T10
Product weight	1.10 g

Lifespan

Product datasheet

Rated lamp life time	2000 h
Number of switching cycles	50000

Additional product data

Base (standard designation)	G4
Mercury content	0.0 mg
Mercury-free	Yes
Predecessor EAN	4050300335162

Capabilities

Burning position	Any
Dimmable	Yes

Certificates & standards

Energy efficiency class	G
Energy consumption	22 kWh/1000h

Country specific categorizations

ILCOS	HSGST/C/UB-20-12-G4-10/22
Order reference	64425 S AX 20W

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075094215	HALOSTAR STARLITE 20 W 12.0 V G4	Shipping carton box 40 Pieces Folding carton box	144 mm x 107 mm x 121 mm	1.86 dm ³	165.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner
of LEDVANCE of LAMPS

OSRAM

OSRAM GmbH
Marcel-Breuer-Strasse 6
80807 Munich, Germany