



# Halogen non-reflector

## 7027 50W G6.35 12V 1CT/10X10F

Halogen non-reflector lamps offer high-quality light and are easy to install, replace and operate. All halogen non-reflector lamps incorporate a distortion-free quartz bulb and a precise positioning of the mounted filament. These ensure optimal beam performance and consistent, high light output. A wide range of wattages is available for a broad variety of applications, including projection systems. In addition you get all the proven advantages of halogen technology such as a full spectrum and a color rendering index (CRI) of 100 – the same as natural light and the best that it can be. Halogen lamps also create a comfortable warm white light, and they maintain their lumen output, with almost no reduction, throughout their lifetime.

#### **Product data**


General Information				
Cap-Base	G6.35 [ G6.35]			
Philips Code	7027			
ANSI Code	BRL-BCD			
LIF Code	A1/220			
Operating Position	S90 [ Standing +/-90D or Base Down (BDH)]			
Main Application	Projection			
Life to 50% Failures (Nom)	50 h			
Light Technical				
Luminous Flux (Rated) (Nom)	1600 lm			
Color Rendering Index (Nom)	100			
Operating and Electrical				
Power (Nom)	50 W			
Voltage (Nom)	12 V			

Mechanical and Housing					
Bulb Material	Quartz-UV Open				
Filament Shape	Flat				
Filament Dimensions WxH	3.3x1.6				
Luminaire Design Requirements					
Bulb Temperature (Max)	900 ℃				
Pinch Temperature (Max)	400 °C				
Product Data					
Full product code	871150040982950				
Order product name	7027 50W G6.35 12V 1CT/10X10F				
EAN/UPC - Product	8711500409829				
Order code	923870217103				
Numerator - Quantity Per Pack	1				
Numerator - Packs per outer box	100				
Material Nr. (12NC)	923870217103				
Net Weight (Piece)	0.002 kg				

Datasheet, 2021, March 19 data subject to change

## Halogen non-reflector

### Dimensional drawing



7027 50W G6.35 12V

Product	D (max)	L (min)	L (max)	L	P (max)	Р	P (min)	C (max)
7027 50W	11.5 mm	29.75	30.25	30	1.05 mm	1 mm	0.95	44 mm
G6.35 12V		mm	mm	mm			mm	
1CT/10X10F								

