

Product datasheetHALOLINE PRO 80 W 230 V R7S

HALOLINE PRO | Double ended halogen lamps with tube base



 General illumination Entrance lighting Pathway lighting Outdoor applications only in suitable luminaires Traffic areas Shops Restaurants, hotels and similar prestigious applications Offices, public buildings Ideal for emphasizing and accentuating the structure of a room

 Brilliant accent lighting Direct replacement for standard tubular halogen lamps Significantly lower CO2 emissions compared to standard version Lower thermal output (compared with the standard reference product) No transformer required Contains no mercury



Product datasheet

Technical data


Certificates & standards

Energy efficiency class	G
-------------------------	---

Environmental information

Date of Declaration	10-11-2021	
Primary Article Identifier	4008321928078	
Candidate List Substance 1	No declarable substances contained	
CAS No. of substance 1	No CAS	
Declaration No. in SCIP database	No declarable substances contained	

Light Distribution



HAL_ohne_UVS

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321928078	HALOLINE PRO 80 W 230 V R7S	Shipping carton box 20 Pieces Folding carton box	112 mm x 77 mm x 92 mm	0.79 dm ³	209.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Product datasheet

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM is distribution partner of LEDVANCE of LAMPS



OSRAM GmbH Marcel-Breuer-Strasse 6 80807 Munich, Germany