



Halogen reflector

JCR 15V 150W H5 24 PACK

Philips' halogen reflector lamps offer the ideal no-fuss solution for a wide variety of medical, projection and scientific illumination systems. Their proven reliability makes them ideal for retrofit installations. The burners are precisely aligned for optimal light performance. Dichroic reflectors ensure heat dissipation towards the back of the optical system, which helps the optical system remain within temperature limits. A special blue-filter version blocking out unwanted light above 700 nm is available for dental curing applications. In addition, you get all the proven advantages of halogen technology such as a CRI of 100 – the same as natural sunlight for the best possible color rendering. Halogen lamps also create a comfortable warm white light, and they maintain their high lumen output with almost no lumen reduction throughout their lifetime.

Product data

General Information	
Cap-Base	GZ6.35 [GZ6.35]
Philips Code	NA [-]
ANSI Code	-
LIF Code	-
Operating Position	S90 [Standing +/-90D or Base Down (BDH)]
Main Application	Fiber optic illumination
Life to 50% Failures (Nom)	500 h
J Code	JCR15V150W5H
Light Technical	
Correlated Color Temperature (Nom)	3100 K
Color Rendering Index (Nom)	100
Operating and Electrical	
Power (Nom)	150 W


Voltage (Nom)	15 V
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Cap-Base Information	-
Bulb Material	Quartz-UV Open
Reflector Finish	Smooth
Filament Shape	-
Filament Dimensions WxH	-
Bulb Shape	R50 [R 50mm]
Luminaire Design Requirements	
Bulb Temperature (Max)	900 °C
Pinch Temperature (Max)	350 °C

Halogen reflector

Working Distance WD	36 mm
Product Data	
Full product code	871150041329130
Order product name	JCR 15V 150W H5 24 PACK
EAN/UPC - Product	8711500413291
Order code	924793618594

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	24
Material Nr. (12NC)	924793618594
Net Weight (Piece)	0.025 kg

Dimensional drawing



JCR 15V 150W 5H

Product	D (max)	C (max)
JCR 15V 150W H5 24 PACK	50 mm	43 mm

